



Durchgangsgewinde




TiN-beschichtet



Außenkühlung

Artikel-Nr.	5736
Norm	DIN 2184-1
Norm	DIN 371 / DIN 376
Schneidstoff	HSS-E-PM
Typ	N
Form	B
Durchmessertoleranz	ISO 2 / 6H
Schneidrichtung	rechts
Rabattgruppe	203

**HSS-E-PM +
TIN
FÜR MAXIMALE
STANDMENGE**



d1	P	d2	SW	dk	l1	l2	l3	Code-Nr.
	mm	mm		mm	mm	mm	mm	
M 2	0,40	2,800	2,10	1,600	45,00	8,00	13,50	2,000
M 3	0,50	3,500	2,70	2,500	56,00	10,00	18,00	3,000
M 4	0,70	4,500	3,40	3,300	63,00	12,00	21,00	4,000
M 5	0,80	6,000	4,90	4,200	70,00	14,00	25,00	5,000
M 6	1,00	6,000	4,90	5,000	80,00	16,00	30,00	6,000
M 8	1,25	8,000	6,20	6,800	90,00	17,00	35,00	8,000
M 10	1,50	10,000	8,00	8,500	100,00	20,00	39,00	10,000
M 12	1,75	9,000	7,00	10,200	110,00	24,00	49,00	12,000
M 14	2,00	11,000	9,00	12,000	110,00	26,00	53,00	14,000
M 16	2,00	12,000	9,00	14,000	110,00	26,00	54,00	16,000
M 18	2,50	14,000	11,00	15,500	125,00	30,00	62,00	18,000
M 20	2,50	16,000	12,00	17,500	140,00	32,00	62,00	20,000

Stückpreis in €
14,30
17,85
16,40
18,25
21,80
24,35
32,15
38,35
58,05
53,90
94,35
97,50

für Durchgangsgewinde

